



# TECHNICAL REGULATIONS FOR FORMULA JUNIOR CARS

These Technical Regulations have been prepared by way of assistance towards Formula Junior competitors. They are intended to be read in conjunction with FIA Appendix K. They should not be considered to be exhaustive.

## NO OTHER MODIFICATIONS ARE PERMITTED

In general, except for what is otherwise explicitly authorised, any part damaged through wear or accident may only be replaced by a part which is identical in specification to (exactly the same as) the one for which it is substituted.

It should be clearly understood that if the following texts do not clearly specify that you can do it, then you should work on the principle that you cannot.

## 1. Principal and abbreviations

ACCUS	The Automobile Competition Committee for the United States.
ASN	A national automobile club or other national body recognised by the FIA as sole holder of sporting power in a country.
CAMS	Confederation Australian Motor Sports. The governing body controlling motor sport in Australia
EU	European Union
FIA	Fédération Internationale de l'Automobile
FJHRA	Formula Junior Historic Racing Association
HC	FIA Heritage Certificate
HTP	Historic Technical Passport
Homologation	Homologation Forms and Recognition Forms endorsed by the FIA
HVIF	Historic Vehicle Identity Form
NEAFP	National Event with Authorised Foreign Participation

The Lurani Trophy is for original Formula Junior cars, run with the original specifications. Cars are single-seater racing cars, whereof the fundamental elements are derived from a touring car recognised as such by the FIA. (Minimum production 1,000 units in twelve consecutive months).

The intention of this championship is to re-create the 1958 - 1963 period of Formula Junior with cars prepared with due consideration to period detail and historical accuracy. General preparation should be to the highest possible standard to match those expected by the FJHRA.

The FIA has created the regulations in Appendix K so that Historic Cars may be used for competitions under a set of rules that preserve the specifications of their period and prevent the modifications of performance and behaviour which could arise through the application of modern technology.

## 2. General

### 2.1. All historic Formula Junior racing is governed by:

- 2.1.1. The original Rules of International Formula Junior 1959 - 1963 copies of which are available from FJHRA and are published on the FJHRA website [www.formulajunior.com](http://www.formulajunior.com)
- 2.1.2. FIA Appendix K - published annually in the FIA Yearbook and on the FIA website (<http://www.fia.com/sport/Regulations>) with amendments published in the FIA monthly bulletin. This document should be read in conjunction with Appendix K.

Appendix K generally requires that all Historic Competition cars will be preserved in the form in which they raced to these rules, except where safety considerations may enforce changes.

- 2.1.3. FIA Appendix J - published annually in the FIA Yearbook and on the FIA website (<http://www.fia.com/sport/Regulations>) Articles 251, 252, 253.
- 2.1.4. The Rules of the FIA Lurani Trophy (where generally applicable) - also published annually in the FIA Yearbook and the FIA website (<http://www.fia.com/sport/Regulations>).
- 2.1.5. These technical regulations which are published by the FJHRA to clarify the FIA Appendix K and Appendix J.
- 2.1.6. Any local variations imposed by local governing bodies.

## **2.2. Competitor eligibility**

- 2.2.1. Entrants where applicable must be in possession of a valid Entrants Licence.
- 2.2.2. Drivers must be fully paid up valid racing members of the FJHRA, [and where applicable, have in addition paid any championship registration fees e.g. for the FIA Lurani Trophy Championship].

## **2.3. Competitor registration**

- 2.3.1. FIA Lurani Trophy Championship
  - 2.3.1.1. All drivers must register as competitors for the FIA Lurani Trophy Championship by returning the completed Registration Form to the Co-ordinator prior to the Final Closing date of the first round being entered.
- 2.3.2. UK FJHRA/HSCC Millers Oils Formula Junior Championship
  - 2.3.2.1. All drivers must be full racing members of the HSCC and register as Competitors for the Championship by returning the Registration Form with the Registration Fee to the Formula Junior Historic Racing Association (FJHRA) prior to the Final Closing date for the first round being entered.

## **2.4. Class structure**

- 2.4.1. Class A FIA Category FJ/1  
Front-engined Formula Junior cars fitted with Fiat or Lancia engines and built and raced before 31.12.1960.
- 2.4.2. Class B FIA Category FJ/1-F  
Front-engined Formula Junior cars built to race before 31.12.1960 (except cars falling within Class A).
- 2.4.3. Class C. FIA Category FJ/1-R  
Rear-engined Formula Junior cars built and raced (or officially entered to race) before 31.12.1960 (except cars falling within Class A). For a list of eligible cars for this class, refer to Annex A.
- 2.4.4. Class D FIA Category FJ/2 Drum Brakes  
Rear-engined and front-engined Formula Junior cars built and raced between 01.01.1961 and 31.12.1963, and fitted with drum brakes on all four wheels, as original specification. For a list of eligible cars for this class, refer to Annex A.
- 2.4.5. Class E FIA Category FJ/2 Disc Brakes  
Rear-engined and front-engined Formula Junior cars built and raced between 01.01.1961 and 31.12.1963, and fitted with a disc brake or brakes.
- 2.4.6. Although FJ2 Formula Junior cars fall within the FIA Period F (1 January 1961 - 31 December 1965), it does not follow that all of the regulations published in Appendix K relating to Period F cars apply retrospectively to FIA Period FJ2 - Formula Junior cars. The Period relating to FJ2 cars ended on 31/12/1963.

## **2.5. Eligibility**

- 2.5.1. Historic Formula Junior is for original Formula Junior racing cars running to the original configuration of that car.
- 2.5.2. To be eligible to race a car must satisfy one of the following three criteria:
  - 2.5.2.1. That car has both an FIA HTP and FIA HVIF in that configuration.

- 2.5.2.2. That car has both an FIA HTP and an FIA HC in that configuration.
- 2.5.2.3. That car has both an FIA HTP and either a CAMS (Confederation of Australian Motorsports) certificate of eligibility; or an HSCC (Historic Sports Car Club) Vehicle Identity Form (issued before 31.12.1999), in that configuration.
- 2.5.2.4. That car has a proven continuous history since period and is in a specification that represents the standard specification for that model [of which there can be only one]; or is in an alternative specification which can be proved by contemporary evidence [documents and/or photographs] as being the period specification for that particular chassis.
- 2.5.3. “CAR” means each and every one of the six principal components.
  - 2.5.3.1. Chassis.
  - 2.5.3.2. Engine - make and model [subject to paragraph 6.4.12. hereof].
  - 2.5.3.3. Gearbox.
  - 2.5.3.4. Brakes.
  - 2.5.3.5. Rear axle.
  - 2.5.3.6. Wheel [diameter].
- 2.5.4. Cars may be permitted to compete at the sole discretion of FJHRA on a PROVISIONAL basis where the Car appears likely to satisfy the criteria of 2.5.3.3. pending complete evidence and documentation.
- 2.5.5. Only genuine and original cars from the correct period will be accepted. Continuation cars or modern replicas are not acceptable.
- 2.5.6. Any car that has been issued with a CAMS certificate of eligibility as an Historic Formula Junior (< 31.12.1963) is eligible to compete in that specification.
- 2.5.7. The following are specific examples (which are NOT exhaustive) of changes that are not permitted.
  - 2.5.7.1. Gemini MkII, BMC engine changed to Ford engine.
  - 2.5.7.2. Elva 100, DKW to BMC engine.
  - 2.5.7.3. Cooper T59, BMC engine to Ford engine.
  - 2.5.7.4. Lotus 18, Renault Dauphine 4 speed gearbox (Type 318) to any other make or type.
  - 2.5.7.5. A Ford engine will not be allowed to be fitted to an Elva 100, except to the one chassis that was so fitted in period.
  - 2.5.7.6. A Stanguellini will only be permitted to use a gearbox with 5 forward ratio’s if it can be proven that the actual chassis was fitted with such a gearbox before the end of Period E.
- 2.5.8. Class B. FIA Category Period E (FJ1) All front engined cars are Period E (FJ1) except except the Mallock U2 Mk 2B and Mk3 which are Period F (FJ2).
- 2.5.9. Appendix K provides that alternative components other than to the manufacturers original specification can only be used if it is proved that these components were used in that particular car in an FIA International event in the Formula Junior period.  
 Thus, as examples, a Ford engine will not be allowed to be fitted to an Elva 100, except to the one chassis that was so fitted in period. A Stanguellini will only be permitted to use a gearbox with 5 forward ratio’s if it can be proven that the actual chassis was fitted with such a gearbox before the end of Period E.
- 2.5.10. Subject to para 2.5.3.2. no car may take part in a Formula Junior race with a specification of a period (class) which is different from the period in which it is classified.

### **3. Date Classification and Definition**

#### **3.1. Date classification**

- 3.1.1. Historic Formula Junior is open to original single seat Formula Junior cars which were manufactured and raced before 31/12/1963.

### **3.2. Period specification**

- 3.2.1. There are several “period specifications” that are relevant to Formula Junior cars. A definition of each period is listed below:
- 3.2.1.1. FIA Period E: (Single-seater cars). 1 January 1947 - 31 December 1960
  - 3.2.1.2. FIA Period F: 1 January 1961 - 31 December 1965
  - 3.2.1.3. FIA FJ1 Period (Classes A,B,C) 1 January 1958 - 31 December 1960
  - 3.2.1.4. FIA FJ2 Period (Classes D,E) 1 January 1961 - 31 December 1963
  - 3.2.1.5. Formula Junior Period 1 January 1958 - 31 December 1963
- 3.2.2. Although FJ2 Formula Junior cars fall within the FIA Period F (1 January 1961 - 31 December 1965), it does not follow that all of the regulations published in Appendix K relating to Period F cars apply retrospectively to FIA Period FJ2 - Formula Junior cars. The Period relating to FJ2 cars ended on 31/12/1963.

## **4. Vehicle Identity Documents**

### **4.1. Historic Technical Passport (HTP)**

- 4.1.1. To compete in the FIA Lurani Trophy for Formula Junior cars, every car shall have an FIA HTP. When the car is presented for scrutineering, the certificate (HTP) as issued by the national sports authority (ASN) concerned must be available and state the origin of its fundamental elements.
- During the year, it is possible that spot-checks will be conducted by the Championships’ Eligibility Scrutineer to ensure continuing compliance with the declared specification on the HTP.
- 4.1.2. To be eligible to obtain an HTP as a Formula Junior car, the car must have been constructed in period to the specification of FIA Formula Junior. It is not necessary for a Formula Junior car to prove International competition history in period.
- 4.1.3. An HTP is strongly recommended but is not obligatory for all cars.
- 4.1.4. An HTP is obligatory for all races in Europe, inserted on the International calendar or the FIA calendar as NEAFP.

## **5. Safety Prescriptions**

### **5.1. General**

- 5.1.1. All of the regulations in this safety section are compulsory.
- 5.1.2. In all respects cars will be required to comply with any general regulations relating to safety as defined within the various sections of these regulations and they will have to comply with any regulations pertaining to the country that the cars would normally compete in.
- 5.1.3. Providing all safety regulations are complied with, if it complies with the original specification the petrol tank, oil tank, battery and fire extinguisher may be located in the driver cockpit space.
- 5.1.4. For FIA races, drivers must comply with the requirements of Appendix L to the International Sporting Code concerning crash helmets, fire resistant clothing and licences.
- 5.1.5. Drivers must wear overalls as well as gloves, long underwear, a balaclava, socks and shoes homologated to the FIA 8856-2000 standard.
- 5.1.6. Drivers must wear gloves in a high-visibility colour which contrasts with the predominant colour of the car, so that the driver can clearly draw the attention of the race starter in case of difficulties.

### **5.2. Condition to take part.**

- 5.2.1. Cars must be presented clean and in a safe condition to take part.

### **5.3. Battery, circuit breaker**

- 5.3.1. Cars must be equipped with a circuit breaker. The circuit breaker, when operated, must stop the engine and isolate all electrical circuits with the exception of those that operate fire extinguishers. The location of the circuit breaker must be identified by a red spark on a white-edged blue triangle (12cm base) and the ‘On’ and ‘Off’ positions clearly marked.

- 5.3.2. The battery earth lead should be identified by a yellow marking.
- 5.3.3. Batteries must be protected to exclude leakage of acid and to protect terminals from short circuiting and producing sparks.
- 5.3.4. Any wet batteries in the driver compartment must be enclosed in a securely located, leak-proof container.

#### **5.4. Pipelines, cables and electrical electrical equipment**

- 5.4.1. All pipes carrying liquid coolant must be clearly marked with red paint, red tape or red heat shrink tubing to give a warning that the pipeline is carrying potentially scalding fluid. Joints should be avoided in the driver cockpit; screwed hose clips may only be used in conjunction with a suitably swaged pipe.
- 5.4.2. It is strongly advised that no fluids shall pass through the chassis tubes in a space frame vehicle.
- 5.4.3. All wiring should be secured and well protected to reduce the risk of fire from electrical shorts.
- 5.4.4. Cars must be equipped with an internal switch that is capable of isolating all electrical circuits (excluding any controlling the fire extinguishers) and completely stopping the engine. The operating switch must be positioned so that it can be operated by the driver when normally seated with seat belts fastened.
- 5.4.5. If a camera/video recorder is carried, the fitting of such equipment must be in position at the time of scrutineering and specifically approved by a scrutineer and the race organisers.

#### **5.5. Fuel system**

- 5.5.1. All safety (bag) tanks must comply with Article 253.14 of current Appendix J (FIA Approved Safety Fuel Tanks).
- 5.5.2. No safety (bag) tank may last over 5 years, unless it has been re-inspected and validated for 2 more years. Manufacturers of such items will issue a certificate and this must be available at scrutineering and upon demand from the FIA steward.
- 5.5.3. All fuel cells have to be date “stamped”. The onus is upon the driver to prove that the cell is “in date”. If the certificate or the manufacturers plate is not available, then the competitor must be prepared to remove the cell in order for the date printed on the walls of the cell to be checked. It is recommended that any safety cell is periodically inspected on a regular basis.
- 5.5.4. For FJ1 cars not fitted with a fuel cell or ‘bag tank’ it is strongly recommended that fuel tanks should be filled with fuel tank safety foam which reduces surge and the risk of explosion. This is mandatory for all FJ2 (Period F) cars.

#### **5.6. Bulkheads**

- 5.6.1. All cars must have a protective bulkhead of non-flammable material between the engine and the driver/passenger compartment. It is recommended that gaps are sealed with GRP or intumescent putty.
- 5.6.2. It is recommended that cars have a bulkhead between any fuel tank and filler and the driver/passenger compartment.

##### **Prohibitions:**

- 5.6.3. The use of magnesium is prohibited for bulkheads.

#### **5.7. Fire extinguisher**

- 5.7.1. All cars must be equipped with at least a hand operated fire extinguisher complying with current Appendix J, Article 253.7.3. [NB: until 31 December 2003 all cars in period F had to have a semi-automatic (driver operated) system, discharging into the engine compartment, conforming to the requirement for open cars in Article 259.14.1 of Appendix J. This is now only optional in the new Appendix K].
- 5.7.2. An extinguishing system homologated by the FIA in accordance with current Appendix J, Article 253.7.2 (Technical List 16) is recommended, with the exception that the external means of triggering required by Article 253.7.2.3 is not mandatory.
- 5.7.3. All plumbed-in extinguisher systems must be FIA homologated and must in be an ‘ARMED’ condition at all times whilst competing or practising.

- 5.7.4. Extinguishers systems should have the weight of the extinguishant, the operating mechanism and the integrity of the cylinder checked and serviced in accordance with the manufacturers instructions. The tare weight of the unit must be marked on the cylinder.
- 5.7.5. The following information must be visible on each extinguisher:
  - 5.7.5.1. The capacity.
  - 5.7.5.2. The type of extinguisher.
  - 5.7.5.3. The tare weight or volume of the extinguisher.
  - 5.7.5.4. The date the extinguisher was last checked, which must be no more than two years after either the date of filling or the date of the last check.
- 5.7.6. All extinguishers must be adequately protected. Their mountings must be able to withstand a deceleration of 25g. Furthermore, in the case of hand held manual extinguishers only quick-release metal fastenings, with metal straps, will be accepted.
- 5.7.7. In the case of manual extinguisher/s they must be easily accessible for the driver.

**Prohibitions:**

- 5.7.8. BCF and Dry powder extinguishant is prohibited.

**5.8. Oil catch tanks**

- 5.8.1. Cars must have any engine oil tank breather or overflow tube venting to atmosphere, led into catch tanks which have a minimum capacity of 2 litres to prevent oil spilling onto the track.

**5.9. Throttles**

- 5.9.1. Additional external throttle return springs must be fitted, one per bank of throttles. The engine must be equipped with a positive method of throttle closing by means of external spring/s so that in the event of failure of any part of the throttle linkage the throttle(s) are sprung closed.

**5.10. Rear-view mirrors**

- 5.10.1. All cars must have at least two mirrors mounted so that the driver has visibility to the rear and both sides of the car. The mirrors shall have a minimum total glass area of 90 cm<sup>2</sup>.

**5.11. Lamps**

- 5.11.1. Not applicable

**5.12. Windscreens**

- 5.12.1. The screen must be to the original size and it may be made of rigid transparent plastic.

**5.13. Roll over hoops**

- 5.13.1. Cars in Period E (Category FJ1) must be fitted with the roll over hoop specified in period, but this may be updated to the roll over hoop specified for Period F cars.
- 5.13.2. For Period F, roll over hoops must conform to Article 277 of Appendix J 1993 as follows:
- 5.13.3. The dimensions of the roll over hoops must be as follows:-
- 5.13.4. The minimum height must be at least 36in (92cm) measured along the straight line following the driver's spine, from the seat's metal shell to the top of the roll over hoop. The top of the roll over hoop must be at least 5cm above the driver's helmet when the driver is sitting in normal driving position. The width must be at least 38cm measured inside the roll over hoop between the two vertical pillars of the sides.
- 5.13.5. It must be measured at 60cm above the seat's metal shell on the perpendicular to the straight line following the driver's spine.
- 5.13.6. In order to provide sufficient strength for towing and lifting possibilities, consideration should be given to the design of the roll over hoop.
- 5.13.7. This specification is recommended for Period E, for which the minimum requirement is that all cars originally fitted with a roll hoop must have roll over hoops meeting or exceeding the specification used on the car when it was used in competition in its period.

**Prohibitions:**

- 5.13.8. Aluminium alloy roll over hoops are prohibited.

#### **5.14. Red rear lights**

- 5.14.1. All cars must be equipped with a working red warning “rain light” facing rearwards. This warning light must be fitted with a bulb of a minimum of 21 watts, with a surface area minimum 20cm<sup>2</sup> with the lens and reflector to EU Standards and must be located within 10cm of the centre line of the car. an alternative light unit of equal or enhance constant luminosity or LED lights that are either homologated by the FIA or comply with relevant EU Regulations may be used. Where LED lights are used, at least 90% of the elements must be operational.

#### **5.15. Safety belts**

- 5.15.1. All seat belts used must be in date and currently homologated by the FIA.
- 5.15.2. FJ1 [Period E] - Seat belts are compulsory if the car has a roll over bar fitted. If no roll over bar is present, then seat belts are recommended but not compulsory, but if they are fitted, then they must be to the same specification as for FJ2.
- 5.15.3. FJ2 [Period F] - FIA homologated seat belts are mandatory.

#### **5.16. Headrests**

- 5.16.1. A headrest/head restraint must be fitted and located such that the drivers head/helmet is restrained and cannot move past it under rearward forces, or be trapped between the roll over bar and the head restraint. It is recommended that it be within 5cm of the driver’s helmet when they are normally seated.

#### **5.17. Engine cover**

- 5.17.1. An engine cover must be fitted and must be adequately fastened.

#### **5.18. Towing-eyes**

- 5.18.1. Cars must have clearly visible towing points clearly marked and identified in yellow. This towing point can be the top of the roll over hoop. Refer to 5.13.6.

#### **5.19. Steering, removable wheel**

- 5.19.1. Whilst it is preferable to retain the original period steering wheel, an alternative steering wheel of different diameter and/or style may be fitted.
- 5.19.2. Although not a period item, in the interests of safety “quick release” steering wheel hubs are permitted.
- 5.19.3. One piece steering columns may be replaced by columns having universal joints or telescopic devices for safety reasons providing that all original functions remain.

#### **5.20. Condition testing**

- 5.20.1. Not required for Formula Junior categories at the present time.

#### **5.21. Repairs**

- 5.21.1. Must be carried out to the original manufacturers standard. Replacement chassis tubes must be the same as the original outside dimension and with the same wall thickness as the original gauge.

#### **5.22. Seats**

- 5.22.1. Original seats are often found to be of inadequate construction. You are recommended to regularly check, strengthen or replace this component with one with a better specification.

## **6. Technical Regulations and Exceptions**

### **6.1. Introduction**

- 6.1.1. The position of FJHRA is simple. Historic Formula Junior races are for original cars, in original specification.
- 6.1.2. All modifications are forbidden unless expressly authorised by these regulations or by the general prescriptions imposed under the heading Article 5 “Safety Prescriptions”.
- 6.1.3. Doubts as to the eligibility of any vehicle or individual component must be clarified in writing by the FJHRA via the Technical Officer.
- 6.1.4. It is the duty of each competitor to satisfy the Scrutineers and the Stewards of the meeting that his automobile complies with these regulations in their entirety at all times during the event.

- 6.1.5. It should be clearly understood that if the following texts do not clearly specify that you can do it, then you should work on the principle that you cannot.

## **6.2. Chassis/Monocoque**

- 6.2.1. The chassis must conform to the original design, dimensions and construction.
- 6.2.2. It is only permitted to strengthen the chassis as required to support roll hoops, seat belt anchors, fire bottles, or any other equipment which increases the safety factor of the vehicle.
- 6.2.3. By way of clarification, the chassis used in all cars must have provenance in conformity with 3.1. If it is necessary to replace or re-build any chassis, then as much material as possible must be retained from the original chassis and it must be grafted in to the 'new' chassis, which itself must be constructed as a direct copy of the original chassis including materials used and the construction methods.

Any manufacturers' original chassis plate must be transferred to the 'new' chassis and the old chassis/sections must be destroyed. It is at all times the responsibility of the competitor to prove provenance on demand of the Technical Officer and all such replacement chassis must be declared by the competitor to the Championship Technical Officer in writing.

- 6.2.4. Any ballast required to achieve the minimum weight must be attached to the chassis in a secure manner in such a way that tools are required for its removal. Provision must be made for the fixation of seals by scrutineers if deemed necessary.
- 6.2.5. The use of "powder-coating" as a protective finish to the chassis is permitted as an alternative to the traditional painted finish.

### **Prohibitions:**

- 6.2.6. Additional strengthening of the chassis/monocoque is not permitted.
- 6.2.7. It is not permitted to change the size outside diameter (O.D.) or thickness (SWG) of the tubing or sheet in the repair of the chassis. The diameter and the gauge of any tubing or sheet used must be as per the original [e.g. if the chassis was originally constructed from Imperial tubing, then any replacement chassis tubes must be Imperial (not metric)].
- 6.2.8. It is not permitted to add any additional triangulation in the form of additional tubes or gussets to the chassis structure.

## **6.3. Front and rear suspension**

- 6.3.1. Suspension e.g. radius arms, wishbones etc. shall not be adjustable unless originally manufactured in this form.
- 6.3.2. If the car is fitted with an "inboard" suspension, the original rocker and shock absorber axis on the chassis must be maintained.
- 6.3.3. The system of suspension (spring type and location of wheels or axles) must not be altered nor must any additional location or springing medium be added unless this was a period specification.
- 6.3.4. Anti-roll bars and telescopic shock absorbers are only permitted if included in the period specification. Anti-roll bars shall be made from a solid bar.
- 6.3.5. Adjustable spring platforms may be used on all cars of which the period specification included concentric coil spring/shock absorber units.
- 6.3.6. Spherical (Rose) joints may only be used if a period specification. Rose joints may also be used on anti-roll bars on period F cars providing that the geometry of the suspension is not affected.
- 6.3.7. Beam and live axles should be of original design must use the same location points and the same shock absorber mounting points.
- 6.3.8. Shock absorbers must be in accordance with Appendix K, ie, to period specifications.
- 6.3.9. Shock absorbers must be steel bodied period items.
- 6.3.10. Shock absorbers must be mounted in the original location using the original mounting points.
- 6.3.11. Suspension bushes may be changed from bonded rubber bushes to 'poly' bushes provided that this does not result in a change in the dimensions.
- 6.3.12. Spherical bearings on shock absorbers are not permitted on Period E cars unless they were a period specification for that car.

**Prohibitions:**

- 6.3.13. It is not permitted to alter the suspension geometry from the original design.
- 6.3.14. It is not permitted to utilise a shock absorber with independent adjustment for bump and rebound (double adjustable).
- 6.3.15. It is not permitted to utilise any single adjustable shock absorber which is gas filled/gas pressurised.
- 6.3.16. It is not permitted to utilise any alloy bodied shock absorber.
- 6.3.17. It is not permitted to utilise any shock absorber with remote reservoirs.

**6.4. Engine****General**

- 6.4.1. The engine components and ancillaries must be of period specification, must be of the same make, model and type fitted and conform to a manufacturer's specification for which period evidence exists.
- 6.4.2. The car must be in the configuration as designed by the manufacturer, with the engine in the original location.
- 6.4.3. Engine tuning is permitted within the following limitations.
- 6.4.4. All of the regulations in this general section apply to all eligible engines.
- 6.4.5. The engine must come from a FIA homologated touring car from FIA Period E or Period F, (up to the end of 1963), the end of the Formula Junior period.
- 6.4.6. The cylinder block, including the cylinder-head and the cylinders (if the latter are removable) must be those of the engine belonging to the car classified by the FIA in the Touring category.
- 6.4.7. The cylinder capacities, specified in the present regulations, may be achieved by modifying the original bore (increase or reduction). No modifications of the stroke are permitted.
- 6.4.8. Swept volume must not exceed 1100cc measured at the point of maximum ring travel.
- 6.4.9. The crankshaft is free, but it must retain the original stroke, refer to 6.4.5.
- 6.4.10. The number of valve ports must conform to a period specification.
- 6.4.11. Although not yet mandatory, it is recommended that all engines should have cross-drilled bolts/nuts/studs sufficient to enable the rocker cover and/or cylinder head and sump pan to be wire sealed to the engine block at any time.
- 6.4.12. The engine specification shall be for the whole period of Formula Junior and shall not be restricted to the period of the two individual categories. For example :-
  - 6.4.12.1. The Ford 109E and 105E engine blocks are both permitted for the FJ/1 categories.
  - 6.4.12.2. 1100cc Ford, B.M.C. and D.K.W. engines are all permitted in the FJ/1 categories in place of similar 1000cc engines, although entrants are encouraged to retain the 1000cc engine where originally fitted to that chassis.
- 6.4.13. Machining, polishing and balancing of the engine parts is authorised.
- 6.4.14. Pistons design is free. Pistons may be altered, or alternative pistons may be used as long as they do not use any modern anti-friction or thermal barrier coatings, see 6.4.26.
- 6.4.15. Valve train, camshafts, valves and valve springs of different specification or manufacture may be used, provided that the number employed does not exceed that of the homologated engine.
- 6.4.16. Connecting rods are free provided they are made of ferrous metal.
- 6.4.17. The use of steel main bearing caps is permitted but the centres of the mounting holes must remain in the original location.
- 6.4.18. The use of higher grade fasteners is permitted. This must be read in conjunction with specific prohibitions listed below.
- 6.4.19. The camshaft is free, but must remain in the manufacturers original position and be the sole means of operating the push rods and valves.
- 6.4.20. Rocker ratio is free.

- 6.4.21. Compression ratio is free, but due consideration should be made to the grade of fuel required by the regulations.
- 6.4.22. The increase of the compression ratio through machining the cylinder head or block, or using a thinner gasket or doing without one, is authorised.
- 6.4.23. Gasket material is free. Modern multi layer steel (MLS) head gaskets are acceptable.

**Prohibitions:**

- 6.4.24. It is not permitted to alter the stroke of the crankshaft.
- 6.4.25. It is not permitted to use non iron cylinder heads and/or engine blocks unless they were homologated in period.
- 6.4.26. It is not permitted to use pistons that utilise any form of modern coating, e.g. ceramic, Xylan/DLC, PTFE (Teflon) or any thermal barrier, low friction, anti-scuffing or similar coating.
- 6.4.27. It is not permitted to use an engine with one or more overhead camshafts.
- 6.4.28. It is not permitted to change the location of the camshaft.
- 6.4.29. In Period E (FJ1), it is not permitted to use a gear driven camshaft, the camshaft must be chain driven.
- 6.4.30. It is not permitted to change the number of crankshaft bearings.
- 6.4.31. It is not permitted to use roller rockers.
- 6.4.32. It is not permitted to use light alloy (aluminium, titanium) valve spring caps/retainers. The material must be magnetic.
- 6.4.33. It is not permitted to use any titanium parts.
- 6.4.34. It is not permitted to use water pump tooth drive belts on FJ1 (Period E) cars. The only acceptable water pump drive belt is the “V” type belt.
- 6.4.35. It is not permitted to use the ribbed (multiple V-belt) drives for the water pump.
- 6.4.36. It is not permitted to use an engine management system.

**Specific regulations**

The following regulations apply to the preparation of engines from the following manufacturers.

**BMC engines**

- 6.4.37. Cars powered by BMC engines may use the cylinder head bearing the casting number 12G940 as a replacement for the original head.
- 6.4.38. The engines allowable are as follows:-

	<b>cc</b>	<b>Stroke</b>	<b>Original Bore</b>
Morris Minor/A35/Sprite	948	76.2mm	62.92mm
Mini Cooper 61-63	997	81.5mm	62.42mm
Morris Minor Sprite/Midget	1098	83.72mm	64.58mm
Mini Cooper XSP FJ	1071	68.26mm	70.61mm

**Prohibitions:**

- 6.4.39. It is not permitted to use a crankshaft with a stroke of 62mm, as used in the Cooper 970 ‘S’ engine from 1964 (F3).

**Fiat engines**

- 6.4.40. Cars powered by Fiat engines may use blocks of the “D” and “R” series, having the serial number 103H, to replace the original 1100/103 block.

**Ford engines**

- 6.4.41. Cars powered by Ford engines must use blocks bearing the casting code 105E or 109E. The use of these blocks is for the whole period of Formula Junior (for example, the Ford 109E and 105E engine blocks are both permitted for FJ/1 category). The use of later, five bearing blocks is prohibited.
- 6.4.42. It is permitted to utilise any of the original equipment Ford pre-crossflow cylinder head castings.
- 6.4.43. The use of the Formula Junior cylinder head manufactured by Geoff Richardson Engineering to the original specification of the Cosworth side draught head is permissible in FJ2 only.
- 6.4.44. Any car in Class B or C fitted with the Richardson head which would otherwise be eligible for these classes but for the Richardson head, shall be admitted to Class D.

## 6.5. Ignition

- 6.5.1. Electronic ignition is permissible on cars built after 31/12/1960 (i.e. FJ2 only) provided that the system utilises contact breaker points or is magnetically coupled (Hall effect switch) and uses a distributor and rotor arm to switch the high tension current and utilises an ignition coil with a minimum resistance of 3 ohms. The Lucas system is the preferred electronic ignition system.
- 6.5.2. A single coil and distributor must be used.
- 6.5.3. An electronic rev limiter may be used for all Historic Formula Junior cars.

### Prohibitions:

- 6.5.4. It is not permitted to use electronic ignition on cars in the FJ1 category.
- 6.5.5. It is not permitted to use a system that uses infra-red optically controlled “breaker” system, in place of the points.

## 6.6. Lubrication

- 6.6.1. The number and type of oil pumps and the length of external oil piping used must conform to period specifications.
- 6.6.2. Fixed or mobile sump baffles and gates are permissible.
- 6.6.3. The oil pump must fitted in its original location. Oil pump drive should be as original.
- 6.6.4. Oil coolers may be fitted if not a period specification, but must be positioned so as not to change the silhouette.
- 6.6.5. The specification of the lubricant utilised is free.
- 6.6.6. The use of oil accumulators are not permitted.

### Prohibitions:

- 6.6.7. It is not permitted to change the system of engine lubrication from wet sump to dry sump for FJ1 category.
- 6.6.8. On wet sump engines (Period FJ1) it is not permitted to use a front mounted oil pump.
- 6.6.9. It is not permitted to fit an electrically driven oil pump.

## 6.7. Fuel system

- 6.7.1. Carburettors from the same or an earlier period may be used, but only if the components are of the same number and general type and principle of operation as those originally fitted.
- 6.7.2. The system and principle of feeding by carburettor or injection, must be the same as on the car from which the engine is taken.
- 6.7.3. It is strongly recommended, that cars of both FJ/1 and FJ2 retain the original make, model and type of carburettors as fitted in period, but subject to the further provisions of this paragraph 10 it is permitted to use a Weber carburettor of period specification to replace an SU or AMAL carburettor.
- 6.7.4. The maximum permissible size of carburettor when a pair of twin sidedraughts are used is 40 eg. 40DCOE.
- 6.7.5. The maximum permissible size of carburettor when a single twin choke sidedraught carburettor is used is a 45.
- 6.7.6. The maximum permissible size of carburettor when a pair of SU's are used is  $1\frac{1}{2}$  inch.
- 6.7.7. The maximum permissible size of carburettor when a single SU carburettor is used  $1\frac{3}{4}$  inch.
- 6.7.8. It is permitted to use the modern reproduction Weber carburettor of Spanish manufacture but to original specification.
- 6.7.9. Air filters are optionasal.
- 6.7.10. Chokes (throat), inlet trumpets, needles and jets sizes are free.
- 6.7.11. The type and specification of the fuel pump/s utilised is free.
- 6.7.12. Only commercial fuel as laid down and defined by the FIA shall be used.
- 6.7.13. With the exception of 2-stoke engines, additional lubricating compounds, not exceeding 2% by volume, may be added to the fuel.

- 6.7.14. Compounds, which are added to fuel to replace lead, may be added if freely available from commercial retailers. The addition of these compounds must not raise the octane value of the unleaded fuel beyond the limit of 90 MON or 102 RON, or leaded fuel beyond 92 MON or 100 RON.
- 6.7.15. The fuel must be commercial petrol which comes from a service station pump, without any additive other than that of a lubricant on current sale. The fuel must comply with FIA specifications:
  - 6.7.15.1. Unleaded fuel 102.0 RON and 90.0 MON maximum
  - 6.7.15.2. Leaded fuel 100.0 RON and 92.0 MON maximum
- 6.7.16. Only air may be mixed with the fuel as an oxidant.
- 6.7.17. Inlet manifolds can be of alloy, steel or stainless steel and can be of cast or welded construction.

**Prohibitions:**

- 6.7.18. It is not permitted to use the Weber 42DCOE or the equivalent size of carburettor from any other manufacturer.
- 6.7.19. It is not permitted to use the the Cosworth/Richardson down draught F3 MAE head. It is only permitted to use down draught carburettors on those cars so fitted in period (eg Terrier T4 S2 or Ausper T4).
- 6.7.20. Forced induction, fuel injection and external slide throttles are prohibited.
- 6.7.21. The fuel tank must not exceed the originally specified capacity.
- 6.7.22. It is not permitted to relocate the position of the fuel tank.
- 6.7.23. It is not permitted to fit a lambda sensor.

## **6.8. Cooling system**

- 6.8.1. Liquid cooling systems are free provided the radiators are within the overall periphery of the vehicle.
- 6.8.2. Any radiator provided by the manufacturer for the model concerned is authorised but its attachment system must not be modified in any way and its position must not be changed
- 6.8.3. The addition of a radiator screen is authorised.
- 6.8.4. Aluminium radiators are permitted.
- 6.8.5. Rubber hoses may be replaced with hoses made from silicon. Where possible, black should be selected in preference to any other available colour.
- 6.8.6. The specification of the coolant utilised is free.

**Prohibitions:**

- 6.8.7. It is not permitted to fit an electrical water pump in place of a mechanical driven one.

## **6.9. Instrumentation**

- 6.9.1. All competitors will be required to fit Electronic Self Identification Modules (transponder) to their cars for the purposes of accurate timing. Holders for these and detailed fitting instructions will be issued with the transponders and it will be the responsibility of the competitor to fit these in the car in the position and manner specified. The Modules must be in place and functioning correctly for all qualifying practice sessions and races. If the car is fitted with the entrant's own permanent transponder, the setting and servicing of these items must only be carried out by properly authorised licensed Timekeepers. Competitors will be charged by the timing company for replacement of the Modules due to misuse or loss.
- 6.9.2. Mechanical tachometers may be replaced with an electronic tachometer and vice versa.

**Prohibitions:**

- 6.9.3. It is not permitted to use any lap timing or datalogging device.
- 6.9.4. It is not permitted to use an Engine Control Unit, (ECU), traction control or launch control device.

## **6.10. Gearbox and transaxles**

- 6.10.1. Subject to paragraph 2.5.2. and paragraphs 6.10.2. and 6.10.3. rear engined cars built after 31/12/1960 (Category FJ2) originally fitted with gearboxes other than Hewland or VW, notwithstanding the general provisions of Appendix K 6.9.5, are not permitted to fit a VW or Hewland gearbox. All cars that have an FIA HVIF in this configuration contrary to period specification are strongly encouraged to revert to their correct and original gearbox.

- 
- 6.10.2. By way of specific exception, a Lotus 20 or a B.M.C. Mk.2 that has not previously held either an FIA HVIF or HTP, and can on evidence prove that the car was fitted with a VW or Hewland gearbox on or before 31 12 2000, may utilize a VW or Hewland gearbox, provided the number of forward speeds is identical to the number used in period.
  - 6.10.3. Rear engined cars built after 31/12/1960 (category FJ2), originally fitted with a VW or Hewland gearbox may use the Hewland Mk6 or Hewland Mk8 gearbox, which utilised the Volkswagen Beetle casing, provided the number of forward speeds is identical to the number used in period. In all cases such cars are encouraged to use the original gearbox.
  - 6.10.4. The number of forward speeds must be identical to the number used in the period. 5 speed gearboxes are only permitted if period evidence exists that one was used in that particular car/chassis.
  - 6.10.5. It is not mandatory to have a reverse gear.
  - 6.10.6. The gearbox specification shall be for the whole of the FJ2 period (for example, if a Hewland gearbox was originally specified by the manufacturer, the Hewland Mark 4, Mark 6 and the Hewland Mark 8 are permitted for FJ/2 category).
  - 6.10.7. Any car in Class A, B or C fitted with an alternative gearbox to the original gearbox, which would otherwise be eligible for these classes but for the alternative gearbox, shall be admitted to Class D.  
When an alternative gearbox is fitted, it must:
    - 6.10.7.1. Comply with the original rules of Formula Junior.
    - 6.10.7.2. Only be a gearbox of the same or an earlier period.
    - 6.10.7.3. The number of forward speeds must be identical to the number used in the period.

**Prohibitions:**

- 6.10.8. Non standard magnesium or light alloy gearbox casings or tail shaft housings are prohibited.
- 6.10.9. It is not permitted to use the Hewland Mark 7 six speed gearbox.
- 6.10.10. It is not permitted to use the Hewland Mark 9 gearbox. This gearbox was not available until 1976.
- 6.10.11. It is not permitted to use a sequential gearbox.

### **6.11. Final drive and clutch**

- 6.11.1. The original clutch control system can be modified. Clutch activation using mechanical means may be converted to hydraulic activation and vice versa.
- 6.11.2. Co-axial hydraulic clutch release systems that utilise an hydraulic release bearing of the direct acting, concentric or co-axial hydraulic slave cylinder type are permitted.

**Prohibitions:**

- 6.11.3. It is not permitted to use a carbon clutch.
- 6.11.4. It is not permitted to use a titanium flywheel.
- 6.11.5. Limited slip differentials are not permitted.
- 6.11.6. If the original fitment, it is not permissible to replace any Metalastic rubber drive shaft “doughnut” drive shaft couplings (Rotoflex) with a replacement universal joint coupling of the Hardy-Spicer type and a sliding splined drive shaft/yoke.
- 6.11.7. It is not permitted to use the modern type of constant velocity joints on the drive shafts.

### **6.12. Brakes**

- 6.12.1. The braking system and principle, ie, drum brakes or discs, must remain the same as on the car from which the engine is taken.
- 6.12.2. Disc brakes are only permitted if a period specification and [with one exception] are only applicable on FJ2 cars. Brake size and type should be as per original specification and should not be increased. This includes both disc and drum-braked cars.
- 6.12.3. Rubber flexible hydraulic pipes may be replaced by smooth bore PTFE (Teflon®) hose with stainless steel outer braid or similar. Where possible, black should be selected in preference to any other available colour.

- 6.12.4. Pressure limiting devices must not be fitted to the hydraulic braking system unless a period specification. Any device allowing the balancing of braking effort between front and rear wheels must not be operable by the driver whilst seated in the driving seat.
- 6.12.5. Brake fluid specification is free.
- 6.12.6. Brake discs must be made from ferrous material.
- 6.12.7. Brake shoe/brake pad material is free.

**Prohibitions:**

- 6.12.8. Vented disc brakes are not permitted. Brake discs must not be modified, i.e. slots and/or grooves in the surface of the disc and cross-drilling is not permitted.
- 6.12.9. Any device operable by the driver, whilst seated in the driving seat which facilitates a change of balance of braking effort between front and rear wheels is not permitted.

**6.13. Wheels (see also 8.1.)**

- 6.13.1. The maximum rim width permitted in Formula Junior is 5 inches (127mm or 5 J) for Period E (FJ1) cars and 6<sup>1</sup>/<sub>2</sub> inches (165mm or 6.5 J) for FIA Period F (FJ2) cars.
- 6.13.2. The above rim widths are MAXIMUM measurements for the category, cars MUST use the same or smaller rim widths as those originally fitted to the car in period.
- 6.13.3. Wheels must be of the same diameter as originally fitted to the car in period.
- 6.13.4. Ospa, these cars may use front and rear wheels with the following maximum dimensions: 4<sup>1</sup>/<sub>2</sub> inches (114mm or 4.5 J) rim width x 15 inch diameter.
- 6.13.5. Wheels may be of a different type from the ones fitted by the manufacturer provided that the hub remains unchanged as well as the dimensions of the rim and the resulting track is identical to the figures stated by the manufacturer.

Where alternative wheels to the originals are utilised, it is strongly recommended that they are visually sympathetic and complementary to the design of the originals.

**Prohibitions:**

- 6.13.6. It is not permitted to fit wheels with a wider rim width than was originally fitted to the car in period.
- 6.13.7. The substitution of wire wheels for disc wheels and vice versa is not permitted.
- 6.13.8. Two-part (split-rim) wheels are not acceptable unless of period specification.

**6.14. Bodywork**

- 6.14.1. All cars must have bodywork to the original silhouette and made from the same material as originally fitted to the car in period.

**Prohibitions:**

- 6.14.2. It is not permitted to substitute aluminium bodywork for G.R.P. bodywork or vice versa.
- 6.14.3. It is not permitted to add additional air ducts, scoops or blisters.
- 6.14.4. No carbon fibre, Kevlar or composite is permitted in any of the bodywork structure.

**6.15. Aerodynamic aids**

**Prohibitions:**

- 6.15.1. No aerodynamic devices may be fitted.

**6.16. Electrical system**

- 6.16.1. All cars must be equipped with a 6 or 12 volt battery and electrically operated self-starter which must be used to start the car.
- 6.16.2. The original location of the battery may be changed but the battery must be securely fixed and have a leakproof cover.
- 6.16.3. The type, the size and capacity of the battery utilised is free.

**6.17. Lighting**

- 6.17.1. Not applicable.

## 6.18. Wheelbase, track, and ground clearance

These regulations MUST be observed.

- 6.18.1. The track and wheelbase must not be altered from the original manufacturer's specification or if this is not available one for which period evidence exists.

The tolerance for the vehicle track is  $\pm 1\%$  and the tolerance for the wheelbase is  $\pm 1.1\%$ , as specified in Appendix K.

- 6.18.2. Minimum track: 110cm.
- 6.18.3. Minimum wheelbase: 200cm.
- 6.18.4. Maximum width of body: 95cm.
- 6.18.5. All sprung parts of the car must have a minimum ground clearance (ride height) of 2.36 inch (60mm), such that a block of 31.5 inch x 31.5 inch x 2.36 inch (800mm x 800mm x 60mm) may be passed underneath the car from any side, at any time of the event. This measurement may be made without the driver but fitted with the wheels and tyres to be used in the competition.
- 6.18.6. The measurement applies to all sprung components, including the "wet" oil sump on Period FJ1 cars, exhaust pipes, inner suspension pick-up points, all bodywork and mounting bolts attached through the floorpan.
- 6.18.7. All measurements must be made while the car is stationary on a flat horizontal surface.

## 6.19. Weight

- 6.19.1. In accordance with the original Rules of Formula Junior (1958-1963).
- 6.19.2. The minimum weight limit is 880lbs (400Kg). This weight limit however is reduced to 794lbs (360Kg) for cars with a cylinder capacity of 1000cc (1000ml) or less. The above-mentioned weights shall be measured with the car in running order, i.e. with all accessories required by these regulations, but with dry fuel tanks.
- 6.19.3. Ballast may be utilised where it is required to meet/exceed the above minimum weight limits. Refer to 6.2.4.

## 7. Supplementary Regulations

### 7.1. Silencer

- 7.1.1. The supplementary regulations of the events may provide that an efficient silencer is compulsory.

### 7.2. Communication

#### Prohibitions:

- 7.2.1. Radio communications between cars and pits are forbidden.

## 8. Tyres

### 8.1. General

- 8.1.1. Tyres for all Formula Junior cars must be Dunlop 'L' section 204 compound and tread pattern CR65 or earlier, except where Dunlop 'L' section tyres are not available for a wheel having a rim width of less than  $3\frac{1}{2}$  inches (88.9mm), road tyres of not lower than 75 profile may be fitted.

**Note:** This only applies to some Stanguellini, Volpini and other early Italian cars].

- 8.1.2. Stanguellini, in order to use 1 inch wider rims at the front, the front track may be increased from 1220mm to 1240mm.
- 8.1.3. Rim widths must not be increased but may be decreased in order to accommodate available tyres. Due regard must be paid to the impact upon the resulting vehicle track, refer to 6.18.1.
- 8.1.4. The interior of the tyre (space between the rim and the internal part of the tyre) must be filled only with air or nitrogen. This does not preclude the use of inner tubes.

#### Prohibitions:

- 8.1.5. It is not permitted to use any tyre heating/heat retention devices.
- 8.1.6. It is not permitted to use tyre or compound treatments.

**9. Final Text**

The final text for these regulations shall be the English version which will be used should any dispute arise over their interpretation.

Any alteration or addition not listed above and which has not been subject to a previous written statement of the entrant will entail a penalty which may go as far as exclusion from the competition without prejudice to higher penalties in case of willful misrepresentation.

**Contacts:**

**Technical Officer:** Grant Wilson

**Co-ordinator/Championship Registrar:** Duncan Rabagliati

FORMULA JUNIOR HISTORIC RACING ASSOCIATION

4 Wool Road, Wimbledon, London SW20 OHW

Telephone: 020 8946 1730

Fax: 020 8946 2367

email: [rabagliati@blueyonder.co.uk](mailto:rabagliati@blueyonder.co.uk)

---



---

**Annex A.**

The following list of classifications for rear-engined drum-braked cars has been prepared. This list is not exhaustive: in respect of any car not listed, the date of the first race appearance shall be the determining factor.

**Class C. FIA Category Period E (FJ/1-R) - Wet sump - Drum Brakes only**

Britannia	Fafnir
Caravelle I	Focus (Mk 1, 2 and 3)
Cooper T52 (Mk 1)	Joker
Cooper T56 (Mk 2)	Kieft
Crossle Mk4	MBM
Deep Sanderson	Moretti
De Sanctis (all models with Fiat engine)	Lotus 18
De Tomaso / ISIS (with Fiat engine)	North Star
Dolphin Mk 1	Sauter DKW
Elva 200	Saxon
Emeryson	Wainer (all models with Fiat engine)
Envoy Mk 1	

**Note:** Any car in the above list fitted with either disc brakes, dry sump, the incorrect gearbox or a Richardson head will be classified in Period F (FJ2) until the specification of that car is corrected.

**Class D. FIA Category Period F (FJ2) - Dry sump - Drum Brakes only**

Alexis Mk 3	Elva 300
Ausper T3	Envoy Mk 2
BMC Mk 2, Mk3, Mk4 and Mk6	Gemini Mk 3 and 3A
Caravelle II and III	Lola Mk 3
Condor SIII	Lotus 20
Dolphin International (Mk 2 and 2A)	Nota #38

## Technical Glossary

### **Adequate Strength**

That the component concerned is of sufficient strength to fulfil the function for which it was intended.

### **Ballast**

Non-functional material added to increase vehicle weight. Any ballast must be permanently fixed to the structure of the vehicle and sealed by Scrutineers' seals.

### **Bodywork :**

All entirely sprung parts of the car in contact with the external air stream, except the roll-over structures and the parts definitely associated with the mechanical functioning of the engine, transmission and running gear. Airboxes and radiators are considered to be part of the bodywork.

### **British Imperial System**

Imperial units or the Imperial system is a collection of units, first defined in the British Weights and Measures Act of 1824, later refined (until 1959) and reduced. The units were introduced in the United Kingdom and its colonies, including Commonwealth countries.

### **Championship**

An event or series of events for the purpose of establishing the right to or collective title.

### **Chassis**

The overall structure of the car around which are assembled the mechanical components and the bodywork including any structural part of the said structure.

### **Co-axial hydraulic clutch release system**

An hydraulic cylinder that fits around the gearbox input shaft.

### **Cockpit**

Structural inner volume which accommodates the driver.

### **Composite**

Material formed from several distinct components, the association of which provides the whole with properties which none of the components taken separately possesses.

### **Cylinder Volume**

The volume swept in cylinder or cylinders by the upward or downward movement of the piston or pistons in relation to such cylinder or cylinders. Cylinder volume shall be expressed in cubic centimetres.

### **Data Acquisition**

The collection and storage of data on a vehicle is termed "data acquisition" or "data logging". Data loggers acquire and store data until the data is downloaded.

### **Driver (Pilot)**

A person nominated as the driver of a vehicle in any event.

### **Driver Instrumentation.**

Driver instrumentation is the medium by which information is displayed to the driver while the vehicle is on the circuit or in the pits/paddock. Driver instrumentation can be driven either by standalone sensors, or driven by a data logger. Sensors to drive the instrumentation are considered as part of the driver instrumentation.

### **Dry Sump**

Any system using a pump to transfer oil from one chamber or compartment to another, to the exclusion of the pump used for the normal lubrication of the engine parts.

### **Engine Compartment**

Volume defined by the structural envelope closest to the engine.

### **Entrant**

The person or body responsible for making an Entry into a Competition and responsible for all matters pertaining to that Entry.

### **Ferrous**

All metals can be classified as Non ferrous metals and Ferrous metals. Ferrous metals are those metals which contain iron and are magnetic e.g. cast iron and steel. Titanium and magnesium are examples of non ferrous metals.

**Forced Induction**

Any device capable of augmenting atmospheric pressure to increase the induction of air or fuel/air mixture into the combustion chamber (Superchargers, Turbochargers etc.). Ram effects entirely due to the forward motion of the vehicle or tuning of induction or exhaust pipe length are not included within this definition.

**“Free” Part**

”Free” means that the original part, as well as its function(s), may be removed or replaced with a new part, on condition that the new part has no additional function relative to the original part.

**Gauge (see also SWG)**

A unit of measurement used for the measurement of thickness sheet and the wall thickness of tubing.

**Ground Clearance**

The clearance between the ground and the lowest part of the bodywork, or of the suspended part of the car, in normal trim.

**G.R.P.**

Glass fibre reinforced plastic.

**Gusset**

A gusset is a device, often triangular, used to reinforce a connection between two components.

**Homologation**

To approve; confirm or ratify and register (a specific make of automobile in general production) so as to make it eligible for international racing competition.

**Imperial**

See British Imperial System.

**Kevlar**

Kevlar is the registered trademark for a light, strong para-aramid synthetic fibre. Kevlar was developed at DuPont in 1965 and it was first commercially used in the early 1970's.

**LED**

A light-emitting diode. Rain lights often use multiple LED's as a small indicator light source.

**Light Alloy**

Any alloy containing more than 10% aluminium, magnesium or titanium.

**Modification**

Any change in the design, material, shape, dimensions and/or surface finish of a component, except for basic manufacturing processes, normal wear and published service or repair procedures.

**MON**

Motor Octane Number (MON) or the aviation lean octane rating, is a better measure of how the fuel behaves when under load. MON testing uses a similar test engine to that used in RON testing, but with a preheated fuel mixture, a higher engine speed, and variable ignition timing to further stress the fuel's knock resistance.

**Monocoque**

A type of construction in which the body is combined with the chassis as a single unit, in which the skin absorbs all or most of the stresses to which the body is subjected.

**O.D.**

Outside Diameter.

**Parc Ferme**

An area designated by and under the control of the organisers and officials of an event into which any entrant or competitor must place the competing vehicle as and when directed by the organizers or officials.

**Poly Bushes**

Modern oil filled shock absorbers are often supplied with poly propylene bushes.

**Ports**

Openings and passages in components forming or housing the combustion chambers and/or cylinders through which ingoing and exhaust gasses pass.

**Powder coating**

Powder coating is a type of dry coating, which is applied as a free-flowing, dry powder. The main difference between a conventional liquid paint and a powder coating is that the powder coating does not require a solvent to keep the binder and filler parts in a liquid suspension form.

**Practice**

That part of an event intended to enable a competitor to familiarize themselves with the course.

**PTFE**

Poly(tetrafluoroethene) or poly(tetrafluoroethylene) (PTFE) is a synthetic fluoropolymer which is found in many applications. PTFE's most well known trademark in the industry is the DuPont brand name Teflon.

**Radiator**

For cooling engine coolants or lubricants (cooler). Not a tank or reservoir.

**RON**

The most common type of octane rating world-wide is the Research Octane Number (RON). RON is determined by running the fuel in a test engine with a variable compression ratio under controlled conditions, and comparing these results with those for mixtures of iso-octane and n-heptane. In most countries the "headline" octane that would be shown on the pump is the RON.

**Silencer**

A sound-reducing device located on an internal combustion engine's exhaust pipe.

**Silhouette**

The outline of the original body shape, in the side and plan view, of the vehicle above a line permitting closure for motor sporting purposes, where the marking for maintaining a time schedule forms a part of the competition.

**Spherical Bearing**

Also known by the following proprietary names, Rose joint (UK and elsewhere), Heims joint (N. America), or a Uniball joint. The ubiquity of these manufacturers in their respective markets led to the terms heim joint and rose joint becoming synonymous with their product.

**Standard wire gauge (SWG)**

British standard wire gauge is a set of wire sizes given by BS 3737:1964, and is generally abbreviated to SWG. Also used for measuring the wall thickness of Imperial size tubing.

**Supplementary Regulations (SR's)**

Compulsory document issued by the Organisers of a competition with the object of laying down the details of that competition.

**Suspension**

The system(s) by which sprung movement is provided between the main chassis structure and the road wheels. Suspension will be deemed to consist of all the partly sprung components that move relative to the main chassis structure for the purpose of making connection between it and the entirely unsprung parts but not including components exclusively concerned with steering, braking and power transmission.

**Sump**

The elements bolted below and to the cylinder block which contain and control the lubricating oil of the engine.

**Telemetry**

Telemetry is the means of transfer of information and/or data from a data source to a data receiver without a cable. In motor sport applications, the term telemetry usually refers to "unidirectional transfer of data to the pits whilst the vehicle is on the circuit, without any acknowledgement signal being transmitted by the pit based equipment.

**Transponder**

In telecommunication, the term transponder (short-for Transmitter-responder) is an automatic device that transmits a predetermined message in response to a predefined received signal. Used for the purpose of lap timing.

**Wet Sump**

A wet sump is a lubricating oil management design for four-stroke piston internal combustion engines which uses a built-in reservoir for oil, as opposed to an external or secondary reservoir used in a dry sump design.

**Wheelbase**

The wheelbase is the horizontal distance between the centre of the front wheel, and the centre of the rear wheel.